


Wireless Loadshackle



- Capacities of 3.25t to 500t, as well as being obtainable up to 3,000t.
- Wireless range of 3,280 ft (328 ft if Bluetooth), (1,640 ft if ATEX/IECEx).
- Every Loadshackle is proof tested.
- Electronics housed in hard anodized enclosure.
- Environmentally sealed to IP67 or NEMA6.
- Battery life of 1,200 hrs from 4 x AA Alkaline batteries (500 hours if Bluetooth).
- Internal antenna.
- Remote on/off from handheld display or software.
- Supplied with a load-centering bobbin.
- 2-year warranty.
- Complies with ASME B30.26.
- Design validated by FEA.
- ATEX Zones 0, 1 & 2 available.
- Bluetooth option is available and is supplied with a free HHP App for iOS and Android.
- Handheld Plus available, but not included.
- Sizes 3.25t to 25t are Crosby 2130 shackles. Size 55t is the 2140 Crosby shackle. Sizes 85t and up are 2135 Crosby shackles.
- Design Factor: 5:1 when used with load bobbin.
- Operating Temperature: 14°F to 122°F.
- Accuracy: $\pm 1\%$ full scale.
- Frequency: 2.4 GHz.
- Data Rate: 3 updates per second.
- Protection: IP67 / NEMA6.



Straightpoint Wireless Loadshackle (WLS)

Stock No.	Model	Capacity (lb)	Resolution (lb)	Weight (lb)	Dimensions (in)									Crosby Shackle
					A	ØB	C	D	E	H	L	N	P	
2789186	WLS3.25T	7,150	10	6.16	1.06	0.75	2.24	0.63	1.69	4.17	5.00	0.69	5.63	G2130
2789200	WLS6.5T	14,300	10	7	1.44	1.00	3.14	0.88	2.28	5.82	6.16	0.97	6.81	G2130
2789183	WLS12T	26,400	20	17.6	2.03	1.38	4.45	1.25	3.25	8.27	7.72	1.38	8.58	G2130
2789185	WLS25T	55,000	50	40	2.87	2.01	6.69	1.75	5.00	12.32	11.06	2.24	11.54	G2130
2789199	WLS55T	120,000	100	55	3.25	2.24	7.47	2.01	5.75	13.70	12.05	2.40	12.48	G2140
2789201	WLS85T	185,000	100	187	4.13	2.76	9.96	2.62	7.24	17.83	14.49	3.11	15.51	S2135
2789172	WLS120T	260,000	200	276	5.00	3.25	12.58	2.99	7.87	21.50	16.06	3.62	17.36	S2135
2789184	WLS200T	440,000	200	573	7.09	4.92	17.02	4.33	11.02	29.06	20.85	4.72	23.62	S2135
2789188	WLS300T	660,000	1,000	893	8.07	5.91	19.88	4.72	12.01	33.94	23.10	5.51	25.87	S2135
2789189	WLS400T	880,000	1,000	1,459	9.06	6.89	21.56	6.30	12.80	37.90	26.27	6.30	30.12	S2135