

Safety Hook GBK

For use with Grade 100 or Grade 80 chain. Safety hook with clevis connector and grab latch.

Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z100758	GBK-6-10	1.5	87	26	15	17	0.4
Z100849	GBK-7-10	2.0	114	36	20	22	0.5
Z100759	GBK-8-10	2.6	119	36	20	22	0.8
Z100760	GBK-10-10	4.0	150	47	22	29	1.4
Z100761	GBK-13-10	6.8	172	53	29	38	2.7
Z100762	GBK-16-10	10.3	208	68	30	45	4.4



4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Safety Hook BKG

For use with Grade 100 or Grade 80 chain. Safety hook with clevis connector and standard latch.

Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z101110	BKG-6-10	1.5	91	29	15	21	0.5
Z101098	BKG-7-10	2.0	120	37	17	22	0.5
Z101100	BKG-8-10	2.6	121	37	17	26	0.9
Z101026	BKG-10-10	4.0	144	45	21	31	1.5
Z101034	BKG-13-10	6.8	180	55	30	40	3.0
Z101042	BKG-16-10	10.3	219	62	37	50	5.5
Z101091	BKG-20-10	16.0	240	68	44	62	9.6
Z101338	BKG-22-10	20.0	276	80	58	62	11.6
Z101343	BKG-26-10	27.3	290	100	67	68	17.8

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.




Safety Hook BKG

For use with Grade 100 or Grade 80 chain. Safety hook with clevis connector and standard latch.

Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z1002401	BKGC-13-10	6.8	164	55	27	43	3.2

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.




Sling Hook GKC

For use with Grade 100 or Grade 80 chain. Sling hook with clevis connector for skip loaders.

Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z7006461	GKC-13-10	6.8	188	60	27	43	2.5

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.



Clevis Egglink CEL

Stock No.	Code	WLL (t)	C	E	G	H	L	Weight (kg)
Z701968	CEL-8-10	2.6	80	40	14	15	100	0.4
Z701969	CEL-10-10	4	100	50	18	19	126	0.7
Z701970	CEL-13-10	6.8	130	65	23	25	162	1.5

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.