

Master Link SKO (open)


For use with Grade 80 chain. For use with SK system.

Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	E	G	K	
Z418683	SKO-7/8-8	2.0	99	50	14	15	0.3
Z418780	SKO-10-8	3.2	127	66	18	20	0.6
Z419383	SKO-13-8	5.4	145	72	22	25	1
Z419480	SKO-16-8	8.2	175	82	25	30	1.5
Z419587	SKO-18/20-8	12.8	204	105	30	36	2.9

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.

Roundsling Coupling SKR

Special shape for full WLL of the roundsling. For use with SK system.




Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	K	
Z127840	SKR-7/8-8	2.0	35	40	13	18	0.2
Z143143	SKR-10-8	3.2	42	47	16	24	0.4
Z302538	SKR-13-8	5.4	50	53	19	29	0.7
Z143240	SKR-16-8	8.2	62	67	23	35	1.3
Z143347	SKR-18/20-8	12.8	71	80	28	43	1.9
Z100057	SKR-22-8	15.5	111	125	40	50	5.3
Z100055	SKR-26-8	21.7	129	150	48	58	8.9

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.

Half-link SKT (includes locking set)

For use with SK system.




Stock No.	Code	WLL (t)	Dimensions (mm)					Weight (kg)
			L	B	F	A	C	
Z426286	SKT-7/8-8	2.0	28	18	9	11	22	0.1
Z426383	SKT-10-8	3.2	34	25	11	13	26	0.2
Z426480	SKT-13-8	5.4	44	30	15	16	33	0.4
Z426587	SKT-16-8	8.2	52	36	19	20	40	0.6
Z426684	SKT-18/20-8	12.8	63	43	22	23	47	1.1
Z100225	SKT-22-8	15.5	76	50	24	26	59	1.7
Z100226	SKT-26-8	21.7	80	58	30	33	61	2.6
Z100227	SKT-32-8	32.8	100	70	38	40	78	4.9

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.

Sling Hook ESKN/SKN with Latch

For use with SK system.



Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z424682	SKN-7/8-8	2.0	90	27	18	21	0.4
Z424789	SKN-10-8	3.2	115	34	23	29	0.8
Z101214	ESKN-13-8	5.4	145	42	28	36	1.8
Z100786	ESKN-16-8	8.2	178	52	36	43	3.4
Z100781	ESKN-18/20-8	12.8	197	54	42	51	5.0

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.