


S-501



- Forged from special bar quality carbon steel, suitable for cold forming.
- Swage socket terminations have an efficiency rating of 100% based on the catalog strength of wire rope.
- Hardness controlled by spheroidize annealing.
- Stamp for identification after swaging without concern for fractures (as per directions in Wire Rope End Terminations User's Manual).
- Swage sockets incorporate a reduced machined area of the shank which is equivalent to the proper 'after swage' dimension. Before swaging, this provides for an obvious visual difference in the shank diameter. After swaging, a uniform shank diameter is created allowing for a QUIC-CHECK® and permanent visual inspection opportunity.
- S-501 Swage Sockets are recommended for use with 6 x 19 or 6 x 37, IPS or XIP (EIP), XXIP (EEIP), RRL, FC or IWRC wire rope.
- In accordance with ASME B30.9, all slings terminated with swage sockets shall be proof loaded. *



S-501 Open Swage Sockets

S-501 and S-501B Open Socket Specifications																	Max. After Swage Dim. (in)	Swager / Die Stock No.		Replacement Round Pin Kit Stock No.	Replacement Bolt/Nut/cot- ter Kit Stock No.
S-501 Stock No.	S-501B Stock No. †	Rope Size		Wt. Each (lb)	Ultimate Load** (t)	Before Swage Dimensions (in)										Tol. +/-		Die Description	Standard		
		(in)	(mm)			A	B	C	D	E	F	H	L	M	N				500 1000 1500 Ton 5 x 7		
1039021	1054001	1/4	6	.52	5.4	4.78	.50	1.38	.69	.27	2.19	.69	4.00	.38	1.47	.06	.46	1/4 Socket	1192845	1083124	1092209
1039049	1054010	5/16	8	1.12	11.8	6.3	.78	1.62	.81	.34	3.25	.80	5.34	.48	1.67	.06	.71	5/16-3/8 Socket	1192863	1083142	1092227
1039067	1054029	3/8	9-10	1.30	13.6	6.3	.78	1.62	.81	.41	3.25	.80	5.34	.48	1.67	.06	.71	5/16-3/8 Socket	1192863	1083142	1092227
1039085	1054038	7/16	11-12	2.08	18.1	7.82	1.01	2.00	1.00	.49	4.31	1.00	6.69	.56	1.96	.06	.91	7/16-1/2 Socket	1192881	1083160	1092245
1039101	1054047	1/2	13	2.08	21.3	7.82	1.01	2.00	1.00	.55	4.31	1.00	6.69	.56	1.96	.06	.91	7/16-1/2 Socket	1192881	1083160	1092245
1039129	1054056	9/16	14	4.67	31.8	9.54	1.27	2.38	1.19	.61	5.38	1.25	8.13	.68	2.21	.06	1.16	9/16-5/8 Socket	1192907	1083188	1092272
1039147	1054065	5/8	16	4.51	34.9	9.54	1.27	2.38	1.19	.68	5.38	1.25	8.13	.68	2.21	.06	1.16	9/16-5/8 Socket	1192907	1083188	1092272
1039165	1054074	3/4	18-20	7.97	43.5	11.61	1.56	2.75	1.38	.80	6.44	1.50	10.00	.80	2.69	.06	1.42	3/4 Socket	1192925	1083204	1092290
1039183	1054083	7/8	22	11.52	51.5	13.37	1.72	3.13	1.63	.94	7.50	1.75	11.63	.94	3.20	.07	1.55	7/8 Socket	1192943	1083222	1092316
1039209	1054092	1	24-26	17.80	71.4	15.47	2.00	3.69	1.81	1.07	8.63	2.00	13.38	1.07	3.68	.08	1.80	1 Socket	1192961	1083240	1092334
1039227	1054104	1-1/8	28	25.25	83.3	17.35	2.25	4.12	2.25	1.19	9.63	2.25	15.00	1.19	4.18	.10	2.05	1-1/8 Socket	1192989	1083268	1092361
1039245	1054113	1-1/4	32	35.56	109	19.2	2.53	4.59	2.50	1.34	10.69	2.50	16.50	1.27	4.68	.10	2.30	1-1/4 Socket	1193005	1083286	2038985
1039263	1054122	1-3/8	34-36	43.75	136	21.1	2.81	5.25	2.50	1.46	11.88	2.41	18.13	1.46	5.25	.10	2.56	1-3/8 Socket	1193023	1083286	2038986
1039281	1054131	1-1/2	38-40	58.50	181	23.17	3.08	5.50	2.75	1.59	12.81	3.00	19.75	1.70	5.70	.10	2.81	1-1/2 Socket	1193041	1083302	1092414
1039307	1054140	1-3/4	44	88.75	228	26.7	3.40	6.25	3.50	1.87	15.06	3.50	23.00	2.11	6.67	.10	3.06	1-3/4 Socket	1193069	1085541	1092441
1042767	1054159	2	48-52	146.2	272	31.15	3.94	7.80	3.75	2.12	17.06	4.00	26.75	1.81	8.19	.10	3.56	2 Socket	1193087	1089985	1092450

S-501 and S-501B Open Socket Specifications					Swager / Die Stock No.			
S-501 Stock No.	S-501B Stock No. †	Rope Size		Die Description	Standard		Side Load	
		(in)	(mm)		500 Ton 1000 Ton 1500 Ton 5 x 7	1500 Ton 3000 Ton 6 x 12	1500 Ton 6 x 12	3000 Ton 6 x 12
1039281	1054131	1-1/2	38-40	1-1/2 Socket	1193041	1191267	1195355	1195192
1039307	1054140	1-3/4	44	1-3/4 Socket	1193069	1191276	1195367	1195209
1042767	1054159	2	48-52	2 Socket	1193087	1191294	1195379	1195218

*Maximum Proof Load shall not exceed 50% of XXIP rope catalog breaking strength. ** The Ultimate Loads of 3/4" through 1 1/4" sizes have been increased to meet the requirements for 8 strand 2160 Grade pendants. † Assembly with bolt, nut and cotter pin. Note: Fittings designed only to be used on exact sizes listed.

NOTE: Before using any Crosby fitting with any other type lay, construction or grade of wire rope, it is recommended that the termination be destructive tested and documented to prove the adequacy of the assembly to be manufactured.