


G-411



- Hot-dip galvanized steel.
- The standard choice for light duty loading conditions and applications.
- Meets the performance requirements of EN13411-1:2002.
- Meets the performance requirements of Federal Specification FF-T-276C Type II, except for those provisions required of the contractor.




Standard Wire Rope Thimbles

Rope Diameter		Stock No	Weight Per 100 (kg)	Dimensions (mm)							
(in)	(mm)			A	B	C	D	E	F	G	H
1/8	3-4	1037256	1.59	49.3	33.3	26.9	17.5	6.35	4.05	1.25	3.30
3/16	5	1037274	1.59	49.3	33.3	26.9	17.5	7.85	5.60	1.25	3.30
1/4	6-7	1037292	1.59	49.3	33.3	26.9	17.5	9.65	7.10	1.25	3.30
5/16	8	1037318	1.81	54.0	38.1	31.8	20.6	11.2	8.65	1.25	3.30
3/8	9-10	1037336	3.04	60.5	41.4	37.3	23.9	13.5	10.4	1.50	4.06
1/2	11-13	1037354	5.67	70.0	47.8	44.5	28.7	17.5	13.5	2.05	4.83
5/8	16	1037372	15.7	89.0	57.0	60.5	35.1	23.1	16.8	3.30	8.64
3/4	18-20	1037390	21.4	95.5	63.5	68.5	41.4	27.4	19.8	3.55	8.64
7/8	22	1037416	38.4	127	89.0	81.0	47.8	32.3	23.9	4.05	11.2
1	24-26	1037434	44.2	145	108	95.5	63.5	35.3	26.9	4.05	10.4
1-1/8 - 1-1/4	28-32	1037452	79	159	114	109	70.0	44.5	33.3	5.60	12.7

G-408



- Hot-dip galvanized steel.
- Meets the performance requirements of EN13411-1:2002.
- Recommended for light duty applications where assembly into another fitting (i.e., shackle or master link) is required.




Open Pattern Thimbles

Rope Diameter		Stock No	Weight Per 100 (kg)	Dimensions (mm)					
(in)	(mm)			A	B	C	D	E	F
1/4	6-7	1037531	1.36	7.10	17.5	26.9	35.8	51.5	9.65
5/16	8	1037559	1.72	8.65	20.6	31.8	38.9	55.0	12.7
3/8	9-10	1037577	3.18	11.2	23.9	37.3	43.7	62.5	15.7
1/2	11-13	1037595	5.67	13.5	28.4	44.5	37.3	72.0	19.1
5/8	16	1037611	11.3	16.8	35.1	60.5	59.5	91.0	25.4

S-412



- Cast ductile iron.
- Fits pin for open wire rope socket, boom pendant clevis, and wedge socket.



Solid Wire Rope Thimbles

Rope Diameter		Stock No	Weight Each (kg)	Dimensions (mm)										
(in)	(mm)			A	B	C	D	E	F	G	H	J	K	L
1/2	13	1037121	.28	71.5	44.5	6.35	26.9	19.1	14.2	7.10	22.4	54.0	41.4	39.6
5/8	16	1037149	1.00	119	76.0	9.65	33.3	26.9	20.6	10.4	28.7	86.0	57.0	65.0
3/4	18-20	1037167	1.05	119	76.0	9.65	38.1	26.9	20.6	10.4	35.1	86.0	57.0	65.0
7/8	22	1037185	2.47	154	97.0	12.7	44.5	35.1	26.9	13.5	41.4	114	82.5	87.5
1	24-26	1037201	2.38	154	97.0	12.7	54.0	35.1	26.9	13.5	46.0	114	82.5	87.5
1-1/8	28-30	1037229	4.21	184	116	16.0	60.5	44.5	33.3	16.8	52.5	137	98.5	103
1-1/4 - 1-3/8	32-35	1037247	4.45	184	116	16.0	67.0	49.3	38.9	19.8	58.5	137	98.5	105