




HG-228

- End fittings are Quenched & Tempered or normalized, bodies heat-treated by normalizing.
- Hot-dip galvanized steel.
- TURNBUCKLES RECOMMENDED FOR STRAIGHT OR IN-LINE PULL ONLY.
- Forged jaw ends are fitted with bolts and nuts for 1/4" through 5/8", and pins and cotters on 3/4" through 2-3/4" sizes.
- Modified UNJ thread on end fittings for improved fatigue properties.
- Body has UNC threads.
- Lock nuts available for all sizes.
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these turnbuckles meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.
- Meets the performance requirements of Federal Specifications FF-T-791b, Type 1 Form 1 - CLASS 7, and ASTM F-1145, except for those provisions required of the contractor. For additional information, see Warnings & Applications.



HG-228 Jaw & Jaw

Thread Dia. & Take Up (in)	Stock No.	Working Load Limit (lb)	Weight Each (lb)	Dimensions (in)									Replacement Pin Kit Stock No.
				00	B	E Closed	G	J Open	K Closed	M Open	N Closed	BB	
* 5/16 x 4-1/2	1032518	800	.56	.25	.50	2.02	.87	13.07	8.57	14.12	9.62	4.58	1089654
* 3/8 x 6	1032536	1200	.85	.31	.53	2.11	.85	16.25	10.25	17.50	11.50	6.10	1089672
1/2 x 6	1032554	2200	1.82	.37	.64	3.22	1.07	18.65	12.65	20.14	14.14	6.03	1089690
1/2 x 9	1032572	2200	2.29	.37	.64	3.20	1.07	24.94	15.94	26.43	17.43	9.36	1089690
1/2 x 12	1032590	2200	2.71	.37	.64	3.20	1.07	30.94	18.94	32.43	20.43	12.36	1089690
5/8 x 6	1032616	3500	3.21	.50	.79	3.90	1.32	19.74	13.74	21.82	15.82	6.03	1089716
5/8 x 9	1032634	3500	3.95	.50	.79	3.89	1.32	26.08	17.08	28.16	19.16	9.39	1089716
5/8 x 12	1032652	3500	4.58	.50	.79	3.89	1.32	32.08	20.08	34.16	22.16	12.39	1089716
3/4 x 6	1032670	5200	4.80	.63	.97	4.71	1.52	21.09	15.09	23.68	17.68	6.13	1097770
3/4 x 9	1032698	5200	5.85	.63	.97	4.68	1.52	27.49	18.49	30.08	21.08	9.59	1097770
3/4 x 12	1032714	5200	6.72	.63	.97	4.68	1.52	33.49	21.49	36.08	24.08	12.59	1097770
3/4 x 18	1032732	5200	8.45	.63	.97	4.71	1.52	45.49	27.49	48.08	30.08	18.53	1097770
7/8 x 12	1032750	7200	9.37	.75	1.16	5.50	1.77	34.65	22.65	37.62	25.62	12.16	1097789
7/8 x 18	1032778	7200	11.8	.75	1.16	5.50	1.77	47.12	29.12	50.09	32.09	18.63	1097789
1 x 6	1032796	10000	10.4	.88	1.34	6.09	2.05	23.82	17.82	27.18	21.18	6.18	1097761
1 x 12	1032812	10000	13.8	.88	1.34	6.09	2.05	35.82	23.82	39.18	27.18	12.18	1097761
1 x 18	1032830	10000	17.1	.88	1.34	6.09	2.05	47.82	29.82	51.18	33.18	18.18	1097761
1 x 24	1032858	10000	21.0	.88	1.34	6.06	2.05	60.42	36.42	63.78	39.78	24.84	1097761
1-1/4 x 12	1032876	15200	21.9	1.13	1.84	8.09	2.82	39.37	27.37	43.58	31.58	12.06	1097798
1-1/4 x 18	1032894	15200	25.9	1.13	1.84	8.09	2.82	51.37	33.37	55.58	37.58	18.06	1097798
1-1/4 x 24	1032910	15200	29.8	1.13	1.84	8.09	2.82	63.93	39.93	68.14	44.14	24.62	1097798
1-1/2 x 12	1032938	21400	32.6	1.38	2.06	8.93	2.81	40.76	28.76	45.68	33.68	12.32	1097805
1-1/2 x 18	1032956	21400	38.0	1.38	2.06	8.93	2.81	52.76	34.76	57.68	39.68	18.32	1097805
1-1/2 x 24	1032974	21400	43.5	1.38	2.06	8.93	2.81	65.38	41.38	70.30	46.30	24.94	1097805
1-3/4 x 18	1033018	28000	53.5	1.63	2.60	9.36	3.35	53.35	35.35	59.16	41.16	18.37	1097814
1-3/4 x 24	1033036	28000	61.1	1.63	2.60	9.36	3.35	65.35	41.35	71.16	47.16	24.37	1097814
2 x 24	1033054	37000	96.3	2.00	2.62	11.80	3.74	69.64	45.64	76.72	52.72	24.48	1097823
2-1/2 x 24	1033072	60000	167	2.25	3.06	13.26	4.44	72.97	48.97	82.18	58.18	24.60	1097832
2-3/4 x 24	1033090	75000	199	2.75	3.69	14.92	4.19	74.75	50.75	85.50	61.50	24.65	1087674

5:1 Design Factor. Proof Load is 2.5 times the Working Load Limit. *Mechanical galvanized