



IPBK10



For the transfer and stacking of steel beams.

- Available in capacities of 0.5 through 4 metric tons.
- Jaw openings available: 0.2 to 1.13”.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Crosby IP logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Minimum WLL of 10% of Maximum WLL.
- For use with materials with a plate surface hardness to 279HV10, only 5% of minimum WLL is needed.
- Maintenance and repair kits are available.
- Temperature range -40 °F (-40 °C) to +212 °F (+100 °C)

Model IPBK10



Model	Working Load Limit (t)*	Stock No.	Weight Each (lb)	Dimensions (in)									Maintenance Kit
				Jaw A	B	C	D	E	F	G	H	J	Stock No.
IPBK10	0.5	2703931	5.29	0.19 - 0.63	1.69	5.28	8.50	1.77	4.72	1.89	1.77	0.39	2715261
IPBK10	1	2703837	5.73	0.19 - 0.63	1.69	5.98	9.06	1.77	4.84	1.85	1.77	0.39	2729234
IPBK10	2	2703838	16.1	0.19 - 1.00	2.44	8.78	13.43	2.76	7.80	2.40	2.76	0.63	2729238
IPBK10	4	2703839	37.3	0.19 - 1.13	2.95	11.10	16.97	3.94	9.13	3.07	2.83	0.79	2729243

Design Factor based on EN 13155 and ASME B30.20.

