



## **Guy Line Blocks**

• Used on guy lines to gain mechanical advantage through rapid take-up, taking less pull to guy down.



459



## **Guy Line Blocks**

Model No.	No. of Sheaves	Stock No.	Working Load Limit (short Tons)	Sheave Diameter (in)	Wire Rope Diameter (in)	Weight Each (lb)
458	1	171619	5	6	1/2	21
458H	1	239067	8	6	9/16 - 5/8	25
459	2	171637	10	6	1/2	28
459H	2	239076	12	6	9/16 - 5/8	31



731

## Double row

**Crown Blocks** 

- McKissick® Roll-Forged sheaves with flame hardened grooves.
- Double row pre-adjusted sealed tapered bearings mounted on a steel shaft.
- Heavy center and side plates for proper support of center pin.
- Pre-assembled units for rapid attachment to crown assembly for installation on derrick.
- On multiple sheave assemblies, one sheave can be grooved for sand line on request.
- · Other sizes available upon request.
- Sheaves manufactured to API-8C specifications.

## **Crown Blocks**



Sheave Diameter (in)	Model No.	Stock No.	No. of Sheaves	Working Load Limit (short Tons)	Wire Rope Diameter (in)	Weight Each (lb)
24	241	351158	1	15	7/8	200
24	242	351167	2	30	7/8	278
24	243	351176	3	45	7/8	375
24	731	351185	1	35	1	200
24	732	351194	2	75	1	350
24	733	351201	3	100	1	525
24	734	351210	4	125	1	720
30	741	351229	1	40	1-1/8	325
30	742	351238	2	80	1-1/8	560
30	743	351247	3	110	1-1/8	800
30	744	351256	4	140	1-1/8	982
30	745	351265	5	170	1-1/8	1163