### **TRY NET BLOCKS**







F-454 6"



8


J-454 8"

APPLICATION AND WARNING INFORMATION SECTION 17

2-7/8

- · Forged steel swivel eyes.
- · Hot-dip galvanized.
- 6" 453 Pressed steel side plates with flared edges. Figure 8 grooved, self-lubricating bronze bushed sheaves, with pressure lube fittings. 453 has an extra wide throat opening to allow fittings to pass through.
- 6" 454 Forged side plates designed to eliminate rope jamming. Wide throat opening and pressure lube fitting on sheave and eye fitting.
- 8" 454 Forged steel side plates designed to eliminate possibility of rope jamming. Furnished with sealed tapered bearings. Flame-hardened forged steel sheaves for wear resistance.

### 453, 454, Blocks



36

8" J-454

Tapered Bearing

## **DOUBLE RIG TRAWL BLOCKS**

10



# **Double Rig Trawl Blocks**

130726

- Steel sheave with flame hardened groove, for maximum wear under abrasive conditions.
- · Double row, permanently sealed tapered roller bearings.
- Pressure lubrication throughout.
- · All steel construction.
- · Hot-dip Galvanized.
- Available in "J" oblong swivel eye and "F" standard swivel eye.



#### J-452 Blocks

Sheave Dia. and Model No.	Stock No.	Working Load Limit (short Tons)	Weight Each (lb)	Sheave Dimensions (in)	
				Outside Diam.	Rim Thickness
8" J-452	130655	10	48	8	3.75
12" J-452	130673	10	85	12	3.75
16" F-452	130682	20	116	16	3.75
18" J-452	2015467	25	300	18	5.44
22" F-452	130708	30	240	22	3.75

4:1 Design Factor.

<sup>4:1</sup> Design Factor.