


LOAD MONITORING

ChainSafe



- Designed to work with 10mm chain.
- Unmatched weight-to-strength ratio.
 - Update rate of 1Hz and the Bluetooth signal effortlessly connects to any iOS or Android smartphone that has our free HHP App that will alert the operator on their smartphone if any overload is occurring.
- Bluetooth wireless range of 100 m.
- No battery change required.
- Battery life: 5 yrs based on 3 hrs use per day.
- Battery Type: Lithium Thionyl Chloride (non replaceable).
- Environmentally sealed to IP67/NEMA6.
- Internal antenna.
- Conforms to EN1677:2008.
- Fatigue tested to 30,000 cycles to 1.5x WLL.
- Design Factor: 4:1.
- Operating Temperature: -10°C to +50°C.
- Recommended Fittings: 10mm (3/8") G100 chain fittings.



		Capacity	Resolution	Weight	Dimensions (mm)						
Stock No.	Model	(t)	(t)	(kg)	Α	В	С	D	E	F	G
2789536	ChainSafe	4	0.002	2.5	164	35	85	132	13.2	11	28

ChainSafe is designed to be fitted with an array of Kito Crosby chain fittings, and is an approved wireless tension loadcell capable of load monitoring of capacities up to 4t.



chain fittings are not included

