


A-350L



- New style incorporates throat opening equal to or larger than old style hooks.
- Each product has a Product Identification Code (PIC) for material traceability, along with a Working Load Limit, and the name Crosby or "CG" forged into it.
- All hooks incorporate Crosby's patented QUIC-CHECK® deformation indicators to help in determining if throat opening dimension has changed.
- Each hook is equipped with a Crosby S-4320 heavy duty stamped latch with the high cycle, long life spring.
- Forged alloy steel, Quenched & Tempered.



4

A-350L Sliding Choker Hook




Single Part Rope Size (in. - mm)	Eight Part Rope Size (mm)	Stock No.	WLL (t)	Weight Each (kg)	Dimensions (mm)													Hook Frame Code	Replacement Latch Kit Stock No.
					A	B	C	D	E	F	G	H	L	P	R	AA*			
3/8 - 10	-	1011802	1.13	.35	52.5	28.7	16.0	61.0	16.0	9.65	21.3	23.1	109	66.0	16.0	38.1	DA	1096325	
1/2 - 13	3	1011811	1.50	.54	57.0	33.3	19.1	75.5	19.8	12.7	24.6	26.9	126	78.5	19.1	38.1	FA	1096374	
† 5/8 - 16	-	1011820	2.27	1.31	77.5	41.4	19.1	90.5	23.9	14.2	28.7	33.3	162	98.5	25.4	50.8	GA	1096421	
† 5/8 - 16	4	1011839	2.27	1.22	77.5	41.4	25.4	90.5	23.9	14.2	28.7	33.3	162	102	28.7	50.8	GA	1096421	
† 3/4 - 20	-	1011848	3.63	2.35	86.0	54.0	25.4	108	29.5	16.0	36.6	41.4	195	116	28.7	63.5	HA	1096468	
† 3/4 - 20	6-7	1011857	3.63	2.27	86.0	54.0	36.6	108	29.5	16.0	36.6	41.4	195	121	28.7	63.5	HA	1096468	
†† 7/8-1 - 22-25	-	1028177	6.75	4.40	112	53.8	31.8	154	35.8	22.4	51.0	59.2	243	145	38.1	76.2	IA	1096515	

*Deformation indicators. †Determine eye diameter "C" before ordering. ††22-25mm is cast steel.

G-3315



- Forged carbon steel, Quenched & Tempered.
- Pressed steel latches and stainless steel springs, bolts and nuts.
- For replacement latch kit, order Stock No. 9900299.
- Hook body - galvanized.
- Suitable for overhead lifting if provisions are made for meeting applicable standards and the specific lifting requirements.



G-3315 Snap Hook



Hook Size (mm)	Stock No.	Working Load Limit (t)	Weight Each (kg)	Dimensions (mm)								Replacement Trigger Kit Stock No.
				A	B	C	D	E	F	L	R	
12	1023056	.34	.11	6.35	19.1	19.1	11.2	57.0	19.1	100	82.5	9900299
14	1023074	.45	.22	8.65	28.4	20.6	14.2	68.5	22.4	120	97.5	9900299

4:1 Design Factor.