




Crosby® Angular Contact Bearing Swivels




- Designed for high rotation speed, lower torque required to initiate rotation.
- Angular contact bearings maximize efficiency, reliability, and service life of swivel and extend the life of the wire rope.
- Entire swivel is zinc plated to resist corrosion.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Hook models utilize genuine Crosby hooks which are forged alloy steel, quenched and tempered, and contain patented QUIC-CHECK® markings.
- Each swivel 7.65 metric tons and larger is furnished with a pressure lubrication fitting.
- For swivels larger than those listed, visit thecrosbygroup.com/engineeredolutions for more information.


AS-1 Jaw & Hook



AS-2 Jaw & Jaw



AS-1 Jaw & Hook



AS-1 JAW & HOOK				Dimensions (mm)									Deformation Indicator AA	Replacement Latch Kit Stock No.	Replacement Bolt Kit Stock No.
Working Load Limit (t)	Wire Rope Size (mm)	Stock No.	Weight Each (kg)	A	B	C	D	E	F	G	H	I			
.40	3	1016001	.32	22.4	6.35	6.35	9.65	10.4	110	72.5	23.6	18.5	38.1	1096325	2018360
.68	6	1016010	.68	33.3	9.65	7.85	11.2	14.2	138	80.0	24.6	21.3	38.1	1096374	2018361
1.35	10	1016025	1.04	41.4	12.7	12.7	17.5	19.8	161	102	29.5	29.0	38.1	1096374	2018362
2.70	13	1016026	2.95	51.0	19.1	19.1	23.9	30.2	221	123	35.8	36.6	63.5	1096374	2018363
4.50	16	1016040	5.85	63.5	22.4	25.4	28.7	38.9	272	160	42.9	46.2	76.0	1096562	2018364
7.65	19	1016045	12.0	76.0	30.2	39.5	34.0	53.0	347	212	61.0	66.0	102	1096657	2018365
9.00	22	1016056	24.0	102	38.1	44.5	44.5	89.0	456	263	81.0	76.0	127	1096704	2018367
13.5	25	1016064	24.0	102	38.1	44.5	44.5	89.0	456	263	81.0	76.0	127	1096704	2018367
22.5	32	1016075	44.0	127	51.0	51.0	60.5	93.5	530	346	82.5	92.0	165	1090161	2018368
31.5	38	1016082	63.5	127	51.0	51.0	60.5	93.5	610	357	76.0	116	178	1090189	2018368

5:1 Design Factor. Individually Proof Tested to 2 times the Working Load Limit.

AS-2 Jaw & Jaw

AS-2 JAW & JAW				Dimensions (mm)								Replacement Bolt Kit Stock No.
Working Load Limit (t)	Wire Rope Size (mm)	Stock No.	Weight Each (kg)	A	B	C	D	E	F	G	H	
.40	3	1016103	.18	22.4	60.5	79.5	9.65	6.35	6.35	4.80	10.4	2018360
.68	6	1016114	.41	33.3	90.0	113	11.2	7.85	9.65	5.60	14.2	2018361
1.35	10	1016122	.91	41.4	103	138	17.5	12.7	12.7	7.10	19.8	2018362
2.70	13	1016131	2.22	51.0	159	207	23.9	19.1	19.1	9.65	30.2	2018363
4.50	16	1016139	4.35	63.5	197	270	28.7	25.4	22.4	13.5	38.9	2018364
7.65	19	1016148	7.17	76.0	245	313	34.0	39.5	30.2	14.2	53.0	2018365
9.00	22	1016157	18.1	102	356	445	44.5	44.5	38.1	20.6	89.0	2018367
13.5	25	1016166	18.1	102	356	445	44.5	44.5	38.1	20.6	89.0	2018367
22.5	32	1016175	35.4	127	405	526	60.5	51.0	51.0	28.7	93.5	2018368
31.5	38	1016184	35.4	127	405	526	60.5	51.0	51.0	28.7	93.5	2018368

5:1 Design Factor. Individually Proof Tested to 2 times the Working Load Limit.