



For Horizontal Lift and Transfer with Pretension System

- Available in capacities of .5 through 12 metric tons (higher Working Load Limits are available upon request).
- Jaw openings available: 0 to 120mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Crosby IP logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.

PHNM10 Horizontal Lifting Clamps



Model	Working Load Limit (Per Pair) (t)*	Stock No.	Weight Each (kg)	Dimensions (mm)										
				Jaw A	B	C	D	E	F	G	H	J	K	L
IPHNM10	0.5	2703287	2.0	0 - 20	81	22	82	16	101	160	74	12	60	4
IPHNM10	1	2703288	3.5	0 - 35	93	30	92	16	103	164	74	12	60	7
IPHNM10	2	2703290	7.5	0 - 30	139	30	131	22	166	245	100	20	74	9
IPHNM10J	2	2703291	8.0	30 - 60	169	30	131	22	166	245	100	20	74	9

*Design Factor based on EN 13155 and ASME B30.20.

Model IPH10 / IPH10J: With Spring Loaded Tension, Magnets and Handle



	Working Load Limit (Per Pair)		Weight Each	Dimensions (mm)									
Model	(t)*	Stock No.	(kg)	Jaw A	B	C	E	F	G	H	J	K	L
IPH10	0.5+	2703297	1.8	0 - 20	86	12	16	103	150	60	12	27	4
IPH10	1+	2703298	2.5	0 - 35	100	16	16	103	150	60	12	31	7
IPH10	2	2703522	5.5	0 - 60	117	16	22	109	256	110	20	40	9
IPH10	3	2703523	7.5	0 - 60	117	20	26	109	266	120	20	48	11
IPH10	4.5	2703524	10.5	0 - 60	132	25	30	104	280	130	20	48	12
IPH10	6	2703525	13.0	0 - 60	143	25	36	123	320	130	20	48	14
IPH10	9	2703526	18.5	0 - 60	157	30	43	133	330	140	25	62	16
IPH10	12	2703527	21.5	0 - 60	172	30	47	141	353	150	25	62	17
With larger jaw opening													
IPH10J	3	2703533	9.0	60 - 120	177	20	26	109	266	120	20	48	11
IPH10J	4.5	2703534	12.0	60 - 120	192	25	30	104	280	130	20	48	12
IPH10J	6	2703535	15.0	60 - 120	203	25	36	123	320	130	20	48	14
IPH10J	9	2703536	20.5	60 - 120	217	30	43	133	330	140	25	62	16
IPH10J	12	2703537	24.0	60 - 120	232	30	47	141	353	150	25	62	17

*Design Factor based on EN 13155 and ASME B30.20.+No handle or magnets.

