



IPBK10



For the transfer and stacking of steel beams.

- Available in capacities of 0.5 through 4 metric tons.
- Jaw openings available: 5 to 28mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Crosby IP logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Minimum WLL of 10% of Maximum WLL.
- For use with materials with a plate surface hardness to 279HV10, only 5% of minimum WLL is needed.
- Maintenance and repair kits are available.
- Temperature range -40 °C (-40 °F) to +100 °C (+212 °F)

Model IPBK10



Model	Working Load Limit (t)*	Stock No.	Weight Each (kg)	Dimensions (mm)									Maintenance Kit Stock No.
				Jaw A	B	C	D	E	F	G	H	J	
IPBK10	0.5	2703931	2.4	5-15	43	134	216	45	120	48	45	10	2715261
IPBK10	1	2703837	2.6	5-15	43	152	230	45	123	47	45	10	2729234
IPBK10	2	2703838	7.3	5-25	62	223	341	70	198	61	70	16	2729238
IPBK10	4	2703839	16.9	5-28	75	282	431	100	232	78	72	20	2729243

Design Factor based on EN 13155 and ASME B30.20.

