


C-Grab CG

For use with Grade 100 or Grade 80 chain. For use with MF master and BK type hooks.




Stock No.	Code	WLL(lb)	Dimensions (in)				Weight (lb)
			L	B	E	D	
B14730	CG-6-10	3,306	3.15	.43	.94	.75	.66
B14731	CG-8-10	5,700	4.21	.47	1.26	.94	1.54
B14732	CG-10-10	8,800	5.28	.59	1.57	1.14	3.31
B14733	CG-13-10	15,000	6.77	.71	2.05	1.50	7.05
B14734	CG-16-10	22,600	8.46	.87	2.52	1.85	13.45

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

C-Grab Duo CGD

For use with Grade 100 or Grade 80 chain. For use with master links.




Stock No.	Code	WLL (lb)	Dimensions (in)				Weight (lb)
			L	B	E	D	
B14720	CGD-6-10	4,700	3.1	.43	.94	.87	1.1
B14721U	CGD-8-10	9,900	4.2	.47	1.3	1.1	2.4
B14722U	CGD-10-10	15,200	5.3	.59	1.6	1.5	4.8
B14723	CGD-13-10	26,000	6.8	.75	1.9	1.9	11.9
B14724U	CGD-16-10	39,100	8.5	.87	2.5	2.2	20.1

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Note: The maximum in service temperature is 392°F.

C-Lok CL

For use with Grade 100 or Grade 80 chain. For use with master links, eye hooks and choke.




Stock No.	Code	WLL (lb)	Dimensions (in)				Weight (lb)
			L	B	E	D	
B14750	CL-6-10	3,306	1.69	.43	.94	.71	.44
B14751	CL-8-10	5,700	2.28	.47	1.26	.94	1.10
B14752	CL-10-10	8,800	2.91	.59	1.57	1.14	2.20
B14753	CL-13-10	15,000	3.70	.71	2.05	1.50	4.41
B14754	CL-16-10	22,600	4.69	.87	2.52	1.89	8.38

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

C-Lok Duo CLD

For use with Grade 100 or Grade 80 chain. For use with master links.



Stock No.	Code	WLL (lb)	Dimensions (in)				Weight (lb)
			L	B	E	D	
B14740	CLD-6-10	5,700	1.69	.43	.94	.87	.88
B14741U	CLD-8-10	9,918	2.28	.47	1.26	1.14	1.32
B14742U	CLD-10-10	15,317	2.91	.59	1.57	1.46	2.65
B14743U	CLD-13-10	26,007	3.70	.71	2.05	1.81	6.83
B14744U	CLD-16-10	39,231	4.69	.98	2.52	2.24	12.13

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Note: The maximum in service temperature is 392°F.