

L-320CN
Frame Size D-N



- Available in carbon steel and alloy steel.
- Eye hooks are load rated (marked with the Working Load Limit).
- Fatigue rated to 20,000 cycles at 1.5 times the Working Load Limit.
- Chemical analysis and tensile tests performed on each PIC to verify chemistry and mechanical properties.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators.
(For detailed information, see the Crosby Value Added page at the beginning of this section.)

L-320C
Frame Size O-T



Load Rated

Fatigue Rated

TA

QUIC-CHECK®

QT

APPLICATION AND WARNING INFORMATION
SECTION 17

L-320N / L-320 Eye Hooks


Working Load Limit (t)		Hook ID Code	Eye Hook Stock No.			Weight Each (kg)	Replacement Latch Kits Stock No.		Open Latch Kit Stock No.
Carbon	Alloy		Carbon L-320C L-320CN S.C.	Carbon GL-320CN Galv.	Alloy L-320A L-320AN S.C.		S-4320	SS-4055	PL
0.75	1.25	†D	1022205	1022208	1022380	.28	1096325	-	-
1	1.6	†F	1022216	1022219	1022391	.40	1096374	-	-
1.6	2.5	†G	1022227	1022230	1022402	.65	1096421	-	-
2	3.2	†H	1022238	1022241	1022413	.94	1096468	-	-
3.2	5.4	†I	1022246	1022249	1022424	1.95	1096515	-	1092000
5	8.0	†J	1022260	1022262	1022435	3.76	1096562	-	1092001
7.5	11.5	†K	1022271	1022274	1022446	6.80	1096609	-	1092002
10	16	†L	1022282	-	1022457	9.42	1096657	-	1092003
15	22	†N	1022293	-	1022468	17.9	1096704	-	1092004
20	31.5	O	1022302	-	1022477	27.2	-	1090161	1093716
25	37	P	1023306	-	1023565	47.6	-	1090189	1093717
30	45	S	1023324	-	1023583	67	-	1090189	1093718
40	60	T	1023342	-	1023609	103	-	1090205	1093719

All carbon hooks have a 5:1 Design Factor. Alloy eye hooks 1t through 22t have a 5:1 Design Factor. Alloy eye hooks 30t through 60t have a 4.5:1 Design Factor. For 3/4t carbon through 22t alloy eye hooks, Proof Load is 2.5 times Working Load Limit. For 20t carbon through 60t alloy eye hooks, Proof Load is 2 times Working Load Limit.

L-320AN
Frame Size D-N



L-320AN
Frame Size O-T



4

Load Rated

Fatigue Rated

TA

QUIC-CHECK[®]

QT

APPLICATION AND WARNING INFORMATION
SECTION 17

L-320N / L-320 Eye Hooks

Hook ID Code*	Dimensions (mm)													
	C	D	F	G	J	K	M	N	O†	O2††	Q	T†	T2††	AA**
†D	85	72.0	31.8	18.5	22.9	16.0	16.0	9.14	22.6	-	19.1	22.1	-	38.1
†F	97	79.0	35.1	21.3	23.6	18.0	18.0	10.7	23.1	-	23.1	24.9	-	50.8
†G	105	89.5	38.1	25.4	25.4	22.4	22.4	14.0	25.4	-	28.7	26.2	-	50.8
†H	119	101	41.4	28.7	28.7	23.9	23.8	14.7	27.7	-	31.8	29.5	-	50.8
†I	147	122	51.0	36.6	37.3	33.3	33.3	18.3	34.5	25.4	39.6	38.9	38.1	63.5
†J	187	159	63.5	46.0	44.5	42.2	42.2	22.9	40.9	33.3	51.0	49.8	47.7	76.2
†K	230	189	76.0	57.0	58.0	47.8	41.4	28.2	53.0	46.0	62.0	62.5	57.2	102
†L	256	211	82.5	66.0	63.5	55.5	49.3	32.3	57.5	51.0	72.0	66.5	58.7	102
†N	318	262	108	76.0	84.0	68.5	60.5	39.6	76.5	69.8	89.0	72.0	65.0	127
O	357	346	127	92.0	102	76.0	76.2	44.5	82.5	-	89.0	87.5	-	165
P	462	357	137	116	108	95.2	81.0	51.0	76.0	-	114	98.5	-	178
S	511	392	152	129	121	114	82.6	55.4	86.0	-	125	121	-	203
T	602	470	178	152	146	140	99.3	64.3	105	-	145	145	-	254

*Deformation indicators. †3/4t carbon though 22t alloy dimensions shown are for S-4320 Latch Kits. Dimensions for "O" frame size and larger are for PL Latch Kits.
††Dimensions are for PL-N latch kits.