

Marine Block Fitting Codes



QG
Swivel Bolt Type
Shackle



QK
Upset Swivel
Bolt Type

CARGO HOISTING BLOCKS



E-566
with Drilled
Swivel Eye

- Block is galvanized.
- Blocks 356mm and larger have flame-hardened roll forged sheaves that assure greater wire life.
- Roll forged sheave is fitted closely into mortise of shell so wire cannot jam between sheave and shell.
- Available for 19mm or 25mm wire.
- Block is fitted with tapered roller bearings which take both load and side thrusts and hold sheave central so it cannot chafe or wear on the sides.
- Tapered Roller bearing with neoprene seals and stainless steel center pin provide long life and trouble-free service.
- Stainless steel center pin has recessed nuts with lock washers.
- Swivel fitting has permanently sealed thrust bearing.
- Pressure lubrication fittings are standard on both center pin and swivel.
- Individually Proof Tested at 4 times Working Load or 2 times Resultant Load.
- A.B.S. recognized load test certificates are furnished.
- Cargo hoist blocks are rated by the maximum single line pull of the wire rope being used.
- Resultant Load equals 2 times single line pull. Ultimate load equals 5 times the Resultant Load.



J-566
with Oblong
Swivel Eye

APPLICATION AND WARNING INFORMATION
SECTION 17

566 Hoisting Blocks

Sheave Size (mm)	E-566 Stock No.	J-566 Stock No.	For QG & QK configuration, add this shackle PN to your E & J Block	Single Line Pull (t)	Wire Rope Diameter (mm)	Weight Each (kg)
305	775003	775209	1019597	4.54	19	43.1
356	775058	775254	1019631	4.54	19	45.4
356	775067	775263	1019631	9.07	25	45.4
406	776609	776672	1019631	9.07	19	59
406	752956	752965	1019631	9.07	25	59

5:1 Design Factor based on Resultant Load. Working Load equals maximum single line pull.