


S-2135 / S-2145



- Trusted Crosby quality.
- Embossed Angle Indicators included.
- Meets performance requirements of Grade 8 shackles.
- 5:1 Design Factor.
- Individually proof loaded to 2 times the Working Load Limit.
- S-2135 and S-2145 shackles are available with aluminum paint and are not galvanized.
- Operating temperature range -20° C (-4° F) to 200° C (392° F) for S-2135 and S-2145.
- Material inspection certificate Type 3.1 according to EN 10204.
- DNV type approved: DNVGL-ST-0377 and DNVGL-ST-0378.
- Meets performance requirements of federal specification RR-C-271H, except for those provisions required of the contractor.
- Meets or exceeds all requirements of ASME B30.26.
- S-2135CT COLD TUFF® available in 85t with an operating temperature range of -60°C (-76°F) up to +200°C (392°F).
- DNV witness proof testing available on request for all sizes and models.
- Magnetic Particle Inspection available on request for all sizes and models.
- Look for the Red Pin®... the mark of genuine Crosby quality.



S-2135 / S-2145 Bolt Type Anchor Shackles

Frame Size (in)	Working Load Limit (t)	Stock No	Weight (kg)	Dimensions (mm)							
				A	+/- 0	B	C	D	R	E	F
S-2135											
3	85	1205009	77	127	+6 / -0	83	330	85	80	190	162
3 1/2	120	1205018	114	144	+6 / -0	95	380	95	89	238	200
4	150	1205027	161	165	+8 / -0	108	385	105	100	275	230
4 3/4	200	1205036	238	180	+8 / -0	125	450	120	110	280	270
5	250	1205045	304	205	+10 / -0	140	520	130	115	305	290
6	300	1205054	365	205	+10 / -0	150	530	140	120	305	315
7	400	1205063	597	230	+10 / -0	175	575	160	160	325	365
7 1/4	500	1205234	729	250	+12 / -0	185	650	180	160	350	385
8	600	1205243	961	275	+13 / -0	205	650	200	185	375	430
8 1/2	800	1205261	1097	300	+15 / -0	220	650	210	200	400	450
9 1/2	1000	1205270	1464	340	+17 / -0	240	700	240	240	420	500
10	1250	1205279	1940	360	+18 / -0	270	750	260	225	450	570
11	1500	1205288	2309	360	+18 / -0	290	800	280	225	450	610
S-2135 CT											
3	85	1205099	77	127	+6 / -0	83	330	85	80	190	162
S-2145											
3	120	1205072	77	127	+6 / -0	83	330	85	80	190	162
3 1/2	150	1205081	114	144	+6 / -0	95	380	95	89	238	200
4	175	1205090	161	165	+8 / -0	108	385	105	100	275	230

Maximum Proof Load is 2.0 times the Working Load Limit.

