


- Made from Quenched & Tempered, Fine Grain Alloy Steel from European Steel Mills.
- Links are individually Proof Tested to values shown, with certification.
- Proof Test with max 60% inside width fixture to prevent localized point loading per ASTM A952.
- Each link is marked with Product Identification Code (PIC) for traceability, Grade, chain size, SWE, GUNNEBO and BG/DGUV manufacturing ID (H32).
- Fatigue rated to at least 20,000 cycles at 1.5 times the Working Load Limit.
- Designed for use with chain, wire or synthetic rope. Applications with wire and synthetic rope generally require a 5:1 Design Factor.
- Fulfills or exceeds requirements in EN 1677:2008 (WLL +25%), ASTM A952/A952M-02, AS 3775:2014 and AS 3776:2015.

Grade 100 Welded Oversized Master Link MFX

Oversized, for 1- and 2-leg slings. Designed for use with CL, CLD, CG and CGD.

Stock No.	Code	WLL (lb)	Proof Load (lbs)	For Grade 100 Chain Size (in)		Dimensions (in)				Weight (lb)
				For chain 1-leg	For chain 2-leg	L	E	D	Flat Thickness	
Z100921	MFX-108-10 GabiQ V2	11,905	19,762	3/8"	5/16"	13.4	7.1	7/8"	5/16"	8.1
Z100922	MFX-1310-10 GabiQ V2	18,078	45,195	1/2"	3/8"	13.4	7.1	1-1/8"	3/8"	10.2
Z100923	MFX-1613-10 GabiQ V2	29,983	74,957	5/8"	1/2"	13.4	7.1	1-1/4"	1/2"	15.4
Z100924	MFX-2016-10 GabiQ V2	45,415	113,538	3/4"	5/8"	13.4	7.1	1-9/16"	5/8"	21.3

5:1 Design Factor.



Master Link MF HDG with Engineered Flat

Stock No.	Code	WLL (lb)		Dimensions (in)			Flat Thickness	Weight (lb)
		EN1677-4	A-952/A952M	L	E	D		
BG14489	MF-86-8 HDG	4,500	5,510	4.72	2.36	.51	7/32"	1.10
BG14482	MF-108-8 HDG	7,100	8,800	5.51	3.15	.67	5/16"	1.76
BG14483	MF-1310-8 HDG	12,000	15,000	6.30	3.74	.87	3/8"	3.31
BG14484	MF-1613-8 HDG	18,000	22,600	7.48	4.33	1.10	1/5"	6.17

5:1 Design Factor.