



LoadSafe (WNI)



- Industry leading wireless range up to 1000m or 3,280ft.
- High grade 17-4PH stainless steel, providing excellent strength and corrosion resistance.
- Frequency: Proprietary 2.4 GHz wireless.
- Accuracy of $\pm 0.1\%$ FS.
- Environmentally sealed to IP67 or NEMA6.
- Stocked capacities up to 1000t.
- Internal antenna.
- ATEX & IECEx version for hazardous area zones 0, 1 & 2 available.
- Battery life of 1200 hrs.
- Compact size.
- Remote on/off from handheld display or software.
- Design validated by FEA.
- Bluetooth option is available and is supplied with a free HHP App for iOS and Android.
- Handheld available, but not included.
- Design Factor: 3:1
- Battery Type: Handheld 2 x AA / Loadcell 4 x AA.
- Operating Temperature: 14°F to 122°F.
- Accuracy: $\pm 0.1\%$ of full scale.
- Battery Life: Handheld - 40 hours / Loadcell 1,200 hours continuous (Loadcell 500 hours if Bluetooth).
- System Range (max): 3,280 ft (328 ft if Bluetooth), (1,640 ft if ATEX/IECEx).



2



Crosby Straightpoint LoadSafe (WNI)

Stock No.	Model	Capacity (lb)	Resolution (lb)	Weight (lb)	Dimensions (in)							
					ØA	B	ØD	E	F	G	H	I
2789197	WNI5TC	11000	2	13.64	3.94	5.00	2.32	0.63	M18 x 2.5	5.98	6.22	0.87
2789191	WNI10TC	22000	5	13.64	3.94	5.00	2.32	0.63	M18 x 2.5	5.98	6.22	0.87
2789193	WNI25TC	55000	10	13.64	3.94	5.00	2.32	0.63	M18 x 2.5	5.98	6.22	0.87
2789196	WNI50TC	110000	20	13.64	3.94	5.00	2.32	0.63	M20 x 2.5	5.98	6.22	0.87
2789190	WNI100TC	220000	100	34	5.98	7.24	3.15	1.02	M20 x 2.5	17.01	8.19	1.30
2789192	WNI150TC	330000	100	34	5.98	7.24	3.15	1.02	M20 x 2.5	17.01	8.19	1.30
2789194	WNI300TC	660000	200	143	7.28	11.81	6.10	1.08	M20 x 2.5	17.01	9.49	1.93
2789195	WNI500TC	1100000	500	143	7.28	11.81	6.10	1.08	M20 x 2.5	17.01	9.49	1.93
2789138	WNI1000TC	2200000	1000	379	14.25	12.20	10.63	1.57	M30 x 3.5	37.40	16.61	4.02