

Crosby Straightpoint Handheld Plus (HHP)



- Displays up to 4 loadcells simultaneously.
- Wireless range 1000m or 3280ft (ATEX 500m or 1640ft).
- Low battery warning.
- Signal strength warning.
- Overload counter.
- User settable 90db audible overload alarm.
- Multiple display units (metric tons, lbs, kg, kN).
- 200Hz peak hold.

2

The Handheld Plus is a rugged and versatile digital handheld display. It has an extensive range of features and is suitable for all Crosby Straightpoint loadcell products.

At the heart of the ergonomically designed Handheld Plus is a powerful PCB, providing industry-leading features such as user selectable units of measure (metric tons, lbs, kg, and kN), programmable audible overload alarm (HHP & SW-HHP), peak hold, pre-set tare, and a user resettable (HHP & SW-HHP) overload counter.

This crucial overload alarm counter is a requirement for many safety and quality control departments because it keeps track of overload events, allowing the loadcell

in question to be removed from service immediately, following the calibration voiding overload event. The loadcell in question can then be sent out for proper testing and, if necessary, recalibration before re-entering service.

The HHP is suitable for connection via cable to any Crosby SP cabled loadcell product and easily adapted to any other manufacturers' loadcell product with a mv/v output.


In addition to the standard HHP the SW-HHP is suitable for connection to any Crosby SP wireless loadcell, has a range of up to 1000m/3280ft (ATEX 500m/1640ft) and is supplied as standard with the Radiolink Plus loadcell.

Stock No.	2789030	2789126	2789442
Model	HHP	SW-HHP	SW-HHP ATEX
Battery Type	2xAA Alkaline	2 x AA	4 x AA Energizer L91
Battery Life	100 Hrs continuous	40 Hrs continuous	40 Hrs continuous
Display Type	240x128 Multi line dot matrix with backlight		
Operating Temp.	-10 to +50 °C / 14 to 122 °F	-20 to +70 °C / -4 to 158 °F	-10 to +50 °C / 14 to 122 °F
Protection	IP65 / NEMA 4X		
Excitation	5v	N/A	N/A
Max Sensitivity	3mv/v	N/A	N/A
Range	N/A	1000 m / 3,280 ft	500 m / 1,640 ft
Connectivity	6-way Female Binder 723 Socket	Wireless 2.4 GHz	Wireless 2.4 GHz

Accessories available for the handheld:

Wall or cab mount bracket
Crosby SP part numbers
SU3282 2789228

Rugged rubber boot
Crosby SP part numbers
SU4045 2789232



Please note:
There is no audible alarm with ATEX