




Wireless

Loadshackles (WLS)



- Capacities of 3.25t to 500t, as well as being obtainable up to 3,000t.
- Wireless range of 1,000 m (100 m if Bluetooth), (500 m if ATEX/IECEx).
- Every Loadshackle is proof tested.
- Electronics housed in hard anodized enclosure.
- Environmentally sealed to IP67 or NEMA6.
- Battery life of 1,200 hrs from 4 x AA Alkaline batteries (500 hours if Bluetooth).
- Internal antenna.
- Remote on/off from handheld display or software.
- Supplied with a load-centering bobbin.
- 2-year warranty.
- Complies with ASME B30.26.
- Design validated by FEA.
- ATEX Zones 0, 1 & 2 available.
- Bluetooth option is available and is supplied with a free HHP App for iOS and Android.
- Handheld Plus available, but not included.
- Sizes 3.25t to 25t are Crosby 2130 shackles. Size 55t is the 2140 Crosby shackle. Sizes 85t and up are 2135 Crosby shackles.
- Design Factor: 5:1 when used with load bobbin.
- Operating Temperature: -10°C to +50°C.



Crosby Straightpoint Wireless Loadshackles (WLS)

Stock No.	Model	Capacity (t)	Resolution (t)	Weight (kg)	Dimensions (mm)										Crosby Shackle
					A	ØB	C	D	E	H	L	N	P		
2789186	WLS3.25T	3.25	0.005	2.8	27	19	57	15	43	106	135	18	150	G2130	
2789200	WLS6.5T	6.5	0.005	3.2	37	25	80	21	58	148	157	25	173	G2130	
2789183	WLS12T	12	0.01	8	52	35	113	30	83	201	201	35	222	G2130	
2789185	WLS25T	25	0.02	18	73	51	170	45	127	313	275	57	290	G2130	
2789199	WLS55T	55	0.05	25	83	57	190	51	146	348	306	61	317	G2140	
2789201	WLS85T	85	0.05	85	127	83	317	80	190	539	393	85	448	S2135	
2789172	WLS120T	120	0.1	125	144	95	364	89	238	624	445	95	488	S2135	
2789184	WLS200T	200	0.2	260	180	125	432	110	280	769	530	120	600	S2135	
2789188	WLS300T	300	0.5	405	205	150	505	120	305	904	587	140	657	S2135	
2789189	WLS400T	400	0.5	662	230	175	548	160	325	1007	667	160	765	S2135	