



LoadSafe (WNI)



- Industry leading wireless range up to 1000m or 3,280ft.
- High grade 17-4PH stainless steel, providing excellent strength and corrosion resistance.
- Frequency: Proprietary 2.4 GHz wireless.
- Accuracy of $\pm 0.1\%$ FS.
- Environmentally sealed to IP67 or NEMA6.
- Stocked capacities up to 1000t.
- Internal antenna.
- ATEX & IECEx version for hazardous area zones 0, 1 & 2 available.
- Battery life of 1200 hrs.
- Compact size.
- Remote on/off from handheld display or software.
- Design validated by FEA.
- Bluetooth option is available and is supplied with a free HHP App for iOS and Android.
- Handheld available, but not included.
- Design Factor: 3:1
- Battery Type: Handheld 2 x AA / Loadcell 4 x AA.
- Operating Temperature: -10°C to $+50^{\circ}\text{C}$.
- Accuracy: $\pm 0.1\%$ of full scale.



2



Crosby Straightpoint LoadSafe (WNI)

Stock No.	Model	Capacity (t)	Resolution (t)	Weight (kg)	Dimensions (mm)							
					ØA	B	ØD	E	F	G	H	I
2789197	WNI5TC	5	0.001	6.2	100	127	59	16	M18 x 2.5	152	158	22
2789191	WNI10TC	10	0.002	6.2	100	127	59	16	M18 x 2.5	152	158	22
2789193	WNI25TC	25	0.005	6.2	100	127	59	16	M18 x 2.5	152	158	22
2789196	WNI50TC	50	0.01	6.2	100	127	59	16	M20 x 2.5	152	158	22
2789190	WNI100TC	100	0.05	15.5	152	184	80	26	M20 x 2.5	432	208	33
2789192	WNI150TC	150	0.05	15.5	152	184	80	26	M20 x 2.5	432	208	33
2789194	WNI300TC	300	0.1	65	185	300	155	28	M20 x 2.5	432	241	49
2789195	WNI500TC	500	0.2	65	185	300	155	28	M20 x 2.5	432	241	49
2789138	WNI1000TC	1000	0.5	172	362	310	270	40	M30 x 3.5	950	422	102