

IP10



For vertical lifting, turning and transfer.

- Available in capacities of .5 through 30 metric tons (higher Working Load Limits are available upon request).
- Wide variety of jaw openings available: 0 to 155mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Crosby IP logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual and test certificate included with each clamp.
- Available in a variety of styles:
 - IP10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
 - IP10J - Larger jaw opening.
 - IP10S - For use with stainless steel material.
 - IP10H - For use with materials with a surface hardness to 472HV10 (450 HB).
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- Maintenance and repair kits are available.
- Minimum WLL is 5% of maximum WLL for .5t IP10 only.
- Minimum WLL is 10% of maximum WLL for all other IP10, IP10J, IP10S, IP10H clamps.
- For plate surface hardness till 279HV10, only 5% of minimum WLL is needed.
- Temperature range -40 °C (-40 °F) to +100 °C (+212 °F)

IP10H



Model IP10 / IP10J / IP10S / IP10H



Model	Working Load Limit (t)*	Stock No.	Weight Each (kg)	Dimensions (mm)										Maintenance Kit Stock No.
				Jaw A	B	C	D	E	F	G	H	J	K	
IP10	0.5	2701674	1.8	0 - 16	44	130	203	40	115	42	28	-	11	2715054
IP10	1	2701662	2.2	0 - 20	45	139	212	40	127	42	38	-	11	2715009
IP10	2	2701676	7.6	0 - 35	78	201	330	70	188	64	55	-	16	2715063
IP10	3	2701664	13.8	0 - 40	100	253	434	75	222	78	60	-	20	2715018
IP10	4.5	2701666	15.0	0 - 40	100	253	434	75	227	82	65	-	20	2715018
IP10	6	2701668	22.8	0 - 50	126	302	517	80	292	84	95	40	20	2715036
IP10	9	2701670	29.8	0 - 50	126	325	544	80	310	94	104	44	25	2715288
IP10	12	2701678	50.4	0 - 54	160	392	574	80	433	121	137	41	25	2715102
IP10	16	2701682	68.0	5 - 64	180	463	686	88	492	121	153	45	25	2715108
IP10	22.5	2701686	108	5 - 80	222	554	803	110	565	153	186	49	25	2715114
IP10	30	2701690	124	5 - 80	222	554	803	110	565	153	186	54	30	2715120
With larger jaw opening														
IP10J	0.5	2701646	1.8	15 - 30	45	128	209	40	128	42	32	-	11	2715054
IP10J	1	2702462	2.5	20 - 40	55	151	207	40	141	42	41	-	11	2715012
IP10J	3	2702458	16.4	40 - 80	115	271	432	75	276	78	67	-	20	2715021
IP10J	4.5	2702460	18.0	40 - 80	115	271	432	75	281	82	72	-	20	2715021
IP10J	6	2701705	25.3	50 - 100	126	302	506	80	336	84	95	40	20	2715040
IP10J	9	2701672	33.1	50 - 100	126	325	542	80	360	94	105	44	25	2715050
IP10J	12	2701680	58.0	54 - 108	178	438	620	80	491	121	136	41	25	2715105
IP10J	16	2701684	80.0	64 - 128	208	521	734	88	562	121	160	45	25	2715111
IP10J	22.5	2701688	130.0	80 - 155	255	628	883	110	660	139	196	49	25	2715117
IP10J	30	2701692	152.0	80 - 155	255	628	887	110	660	153	196	54	30	2715123
For stainless steel - with fixed hoisting eye														
IP10S	0.5	2702274	1.8	0 - 16	44	130	203	40	115	42	28	11	11	2715234
IP10S	1	2702262	2.2	0 - 20	45	139	212	40	127	42	38	11	11	2715243
IP10S	2	2702276	7.6	0 - 35	78	201	330	70	188	64	55	16	16	2715252
IP10S	3	2702264	13.8	0 - 40	100	253	434	75	222	78	60	20	20	2715253
IP10S	4.5	2702266	15.0	0 - 40	100	253	434	75	227	82	65	20	20	2715253
IP10S	6	2702268	23.5	0 - 50	126	302	517	80	292	84	95	20	20	2715254
IP10S	9	2702270	27.5	0 - 50	126	325	544	80	310	94	104	25	25	2715255
For very hard materials - with fixed hoisting eye														
IP10H	0.5	2702174	1.8	0 - 16	44	130	207	40	115	42	28	11	11	2715207
IP10H	0.75	2702162	2.2	0 - 20	45	139	219	40	130	42	38	11	11	2729552
IP10H	1	2702176	7.6	0 - 35	78	201	330	70	188	64	55	16	16	2715216
IP10H	2	2702164	13.8	0 - 40	100	253	434	75	222	78	60	20	20	2715225
IP10H	3	2702166	15.0	0 - 40	100	253	434	75	227	82	65	20	20	2715225
IP10H	4.5	2702168	23.5	0 - 50	126	302	517	80	292	84	95	20	20	2715227
IP10H	6	2702170	27.5	0 - 50	126	325	544	80	310	92	105	25	25	2715229

*Design Factor based on EN 13155 and ASME B30.20.

