

UB-500 Series Top Swiveling Overhaul Balls



With
S320
Eye Hook



With
S1316 A
SHUR-LOC®
Eye Hook



Both styles available with
optional **McKissick®**
Wedge Socket Assembly
or **S-422 TERMINATOR**
Wedge Socket



UWO 422T
TERMINATOR
Wedge Only

- Sizes 4 short Tons through 30 short Tons are available with Crosby's S1316A positive-locking SHUR-LOC® hook, which may be used for lifting personnel. Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Design Factor 4:1
- The top swivel design on the UB-500 assures the ball remains stationary if the wireline spins.
- The swivel incorporates a sealed roller thrust bearing together with a grease fitting for easy lubrication.
- Each ball can be equipped with the new McKissick® US-422T Wedge Socket which can be easily adjusted to fit various sizes of wireline by changing the wedge (ensure that correct wedge is used for selected wireline size).
- All hooks used on UB-500 Overhaul Balls (S320, S320N & S1316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).

Overhaul Ball Assembly

Optional US-422T Wedge Sockets

McKissick® UB-500 Model No.	UB-500 “E” Eye Hook Stock No.	UB-500 “S” SHUR-LOC® Stock No.	Working Load Limit (short tons)	Weight Each (lb)	Wireline Size (in)		Wedge Socket Assy. Stock No.	Weight Each (lb)	Wedge Only Stock No.	Weight Each (lb)
MB4T35E	1036000*	1036005	4	58	3/8	US4T	1044300	4.6	1047310	0.7
MB4T85E	1036009*	1036018	4	102	7/16	US4T	1044309	4.6	1047301	1.0
MB4T150E	1036027*	1036032	4	162	1/2	US4T	1044318	4.6	1047329	1.0
MB4T200E	1036036*	1036041	4	201	1/2	US5T	1044327	8.5	1047338	2.0
MB7T85E	1036045*	1036050	7	109	9/16	US5T	1044336	8.5	1047347	1.8
MB7T150E	1036054*	1036063	7	170	5/8	US5T	1044345	8.5	1047356	1.8
MB7T200E	1036072*	1036077	7	210	5/8	US6T	1044354	9.4	1047365	3.0
MB7T285E	1036081*	1036086	7	321	3/4	US6T	1044363	9.4	1047374	2.5
MB10T150E	1036090*	1036095	10	216	5/8 3/4 7/8 1 1-1/8 1-1/4	US6T US6T US8T US8T US10T US10T	1044354 1044363 1044404 1044417 1044426 1044435	9.4 9.4 20.8 20.8 46.5 46.5	1047365 1047374 1047425 1047431 1047440 1047459	3.0 2.5 5.5 6.1 9.7 10.4
MB10T200E	1036099*	1036108	10	260						
MB10T285E	1036117*	1036122	10	365						
MB10T350E	1036126*	1036131	10	403						
MB10T650E	1036135*	1036140	10	718						
MB12T150E	1036144*	—	12	216						
MB12T200E	1036153*	—	12	258						
MB12T285E	1036171*	—	12	365						
MB12T350E	1036180*	—	12	403						
MB12T650E	1036189*	—	12	718						
MB15T200E	1036198*	—	15	298	5/8 3/4 7/8 1 1-1/8 1-1/4	US8AT US8AT US8T US8T US10T US10T	1044372 1044381 1044404 1044417 1044426 1044435	17.5 17.5 20.8 20.8 46.5 46.5	1047383 1047392 1047425 1047431 1047440 1047459	3.2 3.4 5.5 6.1 9.7 10.4
MB15T350E	1036207*	—	15	456						
MB15T650E	1036216*	—	15	753						
MB15T1150E	1036225*	—	15	1311						
MB20T200E	1036234*	—	20	298						
MB20T350E	1036243*	—	20	456						
MB20T650E	1036252*	—	20	753						
MB20T1150E	1036261*	—	20	1311						
MB25T350E	1036270	—	25	533						
MB25T650E	1036279	—	25	865						
MB25T1150E	1036288	—	25	1421	30	865	1421			
MB30T650E	1036297	—	30	865						
MB30T1150E	1036306	—	30	1421						

4:1 Design Factor. * Utilizes Crosby "N" style hooks with integrated latch. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit. Standard Crosby S-5 Thrust style swivels can not be used with UB-500 Overhaul Balls. For replacement swivels, contact Crosby Customer Service.