

Coupling Link G


For use with Grade 100 or Grade 80 chain. For use with master link and eye hook.

Stock No.	Code	WLL (lb)	Dimensions (in)					Weight (lb)
			L	B	F	A	C	
Z100821	G-6-10	3,306	1.77	.59	.28	.31	.63	.22
Z101358	G-7-10	4,500	2.20	.71	.35	.43	.87	.44
Z100822	G-8-10	5,700	2.20	.71	.35	.43	.87	.44
Z100823	G-10-10	8,800	2.68	.98	.47	.51	1.02	0.66
Z100824	G-13-10	15,000	3.50	1.14	0.59	0.67	1.30	1.54
Z100825	G-16-10	22,600	4.17	1.42	0.75	0.79	1.57	3.09
Z101119	G-20-10	35,300	4.92	1.69	0.91	1.02	1.73	4.85
Z101339	G-22-10	44,080	5.98	1.97	1.02	1.10	2.32	7.72
Z101365	G-26-10	60,169	6.34	2.28	1.26	1.34	2.40	12.57
Z101666	G-32-10	88,160	7.87	2.76	1.50	1.57	3.03	20.94

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M-02 and AS 3776:2015.

Grab Hook GG

Clevis shortening hook. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




Stock No.	Code	WLL (lb)	Dimensions (in)		Weight (lb)
			L	B	
Z101844	GG-6-10	3306	2.13	.31	.44
Z100845	GG-7-10	4500	2.24	.39	.66
B14771	GG-8-10	5700	2.24	.39	.88
B14772	GG-10-10	8800	2.99	.47	1.98
B14773	GG-13-10	15000	3.82	.63	3.97
B14774	GG-16-10	22600	4.49	.79	6.83
Z101152	GG-20-10	35300	5.79	1.02	15.43

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook GG with Locking Pin

Clevis shortening hook with locking pin for extra safety. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




Stock No.	Code	WLL (lb)	Dimensions (in)		Weight (lb)
			L	B	
B14970	GG-6-10 LP	3,306	2.13	.31	0.55
B14971	GG-8-10 LP	5,700	2.24	.39	.88
B14972	GG-10-10 LP	8,800	3.03	.47	1.98
B14973	GG-13-10 LP	15000	3.82	.63	4.19
B14974	GG-16-10 LP	22600	4.49	.79	7.05
B14975	GG-20-10 LP	35,300	5.79	1.02	16.09

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook OG

Eye shortening hook. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.



Stock No.	Code	WLL (lb)	Dimensions (in)				Weight (lb)
			L	B	E	F	
Z101296	OG-7/8-10	5,700	2.56	.39	.67	.39	.66
Z101297	OG-10-10	8,800	3.35	.47	.79	.47	1.54
Z101298	OG-13-10	15,000	4.09	.63	1.02	.63	3.53
Z101299	OG-16-10	22,600	5.16	.79	1.26	.75	6.17
Z101300	OG-20-10	35,300	6.57	1.02	1.61	.91	13.16
Z101301	OG-22-10	44,094	7.36	1.02	1.81	1.26	17.92
Z101302	OG-26-10	60,169	8.98	1.26	2.17	1.50	29.19
Z101303	OG-32-10	88,160	9.02	1.57	1.97	1.06	45.57

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.