



S-319/S-319N









S-319 / S-319N Shank Hook

Hook ID Code	Dimensions (mm)																	
	D	F	G	H	J	K	L	M	O	O2 ††	P	R	T	T2 ††	X	Y	Z	AA*
†D	72.6	31.8	18.5	20.6	23.6	16.0	131	16.0	†23.4	-	49.5	59.9	21.6	-	16.0	52.3	17.5	38.1
†F	80.0	35.1	21.3	23.9	24.6	18.0	144	18.0	†24.4	-	56.4	65.8	24.4	-	19.3	57.2	19.8	50.8
†G	91.2	38.1	25.4	29.5	26.9	22.4	162	22.4	†26.9	-	62.2	70.4	25.9	-	22.4	65.8	22.4	50.8
†H	101	41.4	28.7	33.3	30.2	23.9	181	23.9	†29.2	-	70.6	80.3	29.2	-	22.4	72.1	25.4	50.8
†I	123	50.8	36.6	41.4	38.1	33.3	219	28.7	†35.8	30.2	88.1	97.8	35.8	35.1	29.5	84.8	31.8	63.5
†J	159	63.5	46.0	52.3	45.2	42.2	265	36.6	†42.9	35.1	116	121	49.0	46.0	35.8	97.5	39.6	76.2
†K	192	76.2	57.2	66.8	61.2	47.8	318	41.4	†56.4	47.5	133	149	58.9	55.6	46.0	111	49.3	102
†L	212	82.6	65.8	74.7	66.5	55.6	406	49.3	†61.5	50.3	150	162	61.5	58.4	50.8	178	55.6	102
†N	264	108	76.2	88.9	86.6	68.3	461	60.5	†80.5	69.9	174	207	70.6	68.3	65.0	178	66.8	127
O	346	127	93.0	118	102	76.2	586	76.2	83.1	-	223	238	86.4	-	79.5	254	79.5	165
O	346	127	93.0	118	102	76.2	790	76.2	83.1	-	223	238	86.4	-	79.5	457	79.5	165
P	357	137	118	127	108	91.9	816	81.0	83.3	-	289	318	95.8	-	102	381	102	178
P	357	137	118	127	108	91.9	1044	81.0	83.3	-	289	318	95.8	-	102	610	102	178
S	392	152	130	140	121	94.5	867	82.6	91.9	-	321	356	122	-	106	381	106	203
S	392	152	130	140	121	94.5	1095	82.6	91.9	-	321	356	122	-	106	610	106	203
T	469	178	154	165	146	113	916	99.3	115	-	376	394	145	-	114	368	114	254
T	469	178	154	165	146	113	1208	99.3	115	-	376	394	145	-	114	660	114	254
U	524	197	172	184	165	133	1045	108	125	-	420	492	149	-	127	381	127	292
U	524	197	172	184	165	133	1248	108	125	-	420	492	149	-	127	584	127	292
W	583	173	221	251	149	140	1070	140	114	-	441	468	168	-	178	381	178	305
W	583	173	221	251	149	140	1222	140	114	-	441	468	168	-	178	533	178	305
X	618	171	238	278	152	152	1162	152	117	-	449	467	169	-	200	457	200	330
Y	678	191	254	299	168	178	1283	178	126	-	501	521	193	-	203	508	203	330
X	765	241	278	328	203	184	1459	184	181	-	181	576	597	-	241	584	241	381

Rough as-forged dimension. Shank will not machine to this dimension. Please refer to the warnings & applications section for recommended shank diameter when machining.
*Deformation indicators. †3/4t carbon through 22t alloy dimensions shown are for S-4320 Latch Kits. Dimensions for "O" frame size and larger are for PL Latch Kits. ††Dimensions are for PL-N latch kits. For the purpose of calculating D/d ratio, utilize dimension M.

© 2027 CMCO. All Rights Reserved.